



Optional Accessories:



Motor Power	Discharge Bore	Max.Output	Liter/mim	Lift / Meter	kg / cm ²	Approx. Weight (kg)
		(Single ph)	(Three ph)	(Single ph)	(Three ph)	
1/10 HP (0.07 KW)	1/4" PT	10	13	0.35	0.4	2.8
	3/8" PT	23	26	0.3	0.35	
SP - 013012 1/10 HP (0.07 KW)	1/4" PT	9	12	0.3	0.35	2.9
	3/8" PT	20	22	0.25	0.3	
SP - 0130ST2 1/10 HP (0.07 KW)	1/4" PT	9	12	0.3	0.35	3.1
	3/8" PT	20	22	0.25	0.3	
1/8 HP (0.09 KW)	3/8" PT	37	40	0.47	0.5	3.7
	1/2" PT	43	48	0.43	0.48	
1/6 HP (0.13 KW)	3/8" PT	39	43	0.53	0.56	4.3
	1/2" PT	46	52	0.49	0.54	
1/4 HP (0.18 KW)	1/2" PT	74	77	1	1.1	7.1
	3/4" PT	81	85	0.9	1.05	
1/3 HP (0.25 KW)	3/4" PT	-	95	-	1.2	7.9
	1" PT	141	150	1.2	1.4	
1/2 HP (0.37 KW)	1" PT	151	165	1.1	1.3	8.9
	1" PT	-	180	-	1.43	
3/4 HP (0.56 KW)	1" PT	-	230	-	1.7	10.4
	1" PT	-	250	-	1.6	
1 HP (0.75 KW)	1" PT	-	250	-	1.6	12.6
	1" PT	-	250	-	1.6	
1.5 HP (1.12 KW)	1" PT	-	285	-	1.8	15
	1" PT	-	285	-	1.8	

Dimensional code:



Unit : mm

Model No.	HP (KW)	H	L	A	B	C	D	E	F	PCD	W
SP - 8100	1/8 (0.09)	250	100	7.2	69	106	97	124	156	115~129	7.2
SP - 8130	1/8 (0.09)	280	130	7.2	69	106	97	124	156	115~129	7.2
SP - 8150	1/8 (0.09)	300	150	7.2	69	106	97	124	156	115~129	7.2
SP - 8180	1/8 (0.09)	330	180	7.2	69	106	97	124	156	115~129	7.2
SP - 8200	1/8 (0.09)	350	200	7.2	69	106	97	124	156	115~129	7.2
SP - 8220	1/8 (0.09)	370	220	7.2	69	106	97	124	156	115~129	7.2
SP - 8270	1/8 (0.09)	420	270	7.2	72	106	97	124	156	115~129	7.2
SP - 6100	1/6 (0.12)	250	100	7.2	69	106	97	124	156	115~129	7.2
SP - 6130	1/6 (0.12)	280	130	7.2	69	106	97	124	156	115~129	7.2
SP - 6150	1/6 (0.12)	300	150	7.2	69	106	97	124	156	115~129	7.2
SP - 6180	1/6 (0.12)	330	180	7.2	69	106	97	124	156	115~129	7.2
SP - 6200	1/6 (0.12)	350	200	7.2	69	106	97	124	156	115~129	7.2
SP - 6220	1/6 (0.12)	370	220	7.2	69	106	97	124	156	115~129	7.2
SP - 6270	1/6 (0.12)	420	270	7.2	69	106	97	124	156	115~129	7.2

Unit : mm

Model No.	HP (KW)	H	L	A	B	C	D	E	F	PCD	W
SP - 4130	1/4 (0.18)	310	130	8	69	133	120	160	189	148~163	9
SP - 4155	1/4 (0.18)	335	155	8	69	133	120	160	189	148~163	9
SP - 4180	1/4 (0.18)	365	180	8	69	133	120	160	189	148~163	9
SP - 4200	1/4 (0.18)	385	200	8	69	133	120	160	189	148~163	9
SP - 4220	1/4 (0.18)	405	220	8	69	133	120	160	189	148~163	9
SP - 4240	1/4 (0.18)	425	240	8	69	133	120	160	189	148~163	9
SP - 4270	1/4 (0.18)	455	270	8	69	133	120	160	189	148~163	9
SP - 4350	1/4 (0.18)	535	350	8	69	133	120	160	189	148~163	9
SP - 3155	1/3 (0.25)	335	155	8	98	133	120	160	189	148~163	9
SP - 3180	1/3 (0.25)	365	180	8	98	133	120	160	189	148~163	9
SP - 3200	1/3 (0.25)	385	200	8	98	133	120	160	189	148~163	9
SP - 3220	1/3 (0.25)	405	220	8	98	133	120	160	189	148~163	9
SP - 3240	1/3 (0.25)	425	240	8	98	133	120	160	189	148~163	9
SP - 3270	1/3 (0.25)	455	270	8	98	133	120	160	189	148~163	9
SP - 3350	1/3 (0.25)	535	350	8	98	133	120	160	189	148~163	9
SP - 2150	1/2 (0.37)	370	150	8.5	69	145	136	168	199	150~180	10
SP - 2180	1/2 (0.37)	400	180	8.5	69	145	136	168	199	150~180	10
SP - 2240	1/2 (0.37)	460	240	8.5	69	145	136	168	199	150~180	10
SP - 2290	1/2 (0.37)	510	290	8.5	69	145	136	168	199	150~180	10
SP - 2340	1/2 (0.37)	560	340	8.5	69	145	136	168	199	150~180	10
SP - A150	3/4 (0.56)	370	150	8.5	98	145	136	168	199	150~180	10
SP - A180	3/4 (0.56)	400	180	8.5	98	145	136	168	199	150~180	10
SP - A240	3/4 (0.56)	460	240	8.5	98	145	136	168	199	150~180	10
SP - A290	3/4 (0.56)	510	290	8.5	98	145	136	168	199	150~180	10
SP - A340	3/4 (0.56)	560	340	8.5	98	145	136	168	199	150~180	10
SP - I180	1 (0.75)	420	180	10	69	162	154	190	215	169~201	10.2
SP - I240	1 (0.75)	480	240	10	69	162	154	190	215	169~200	10.2
SP - I290	1 (0.75)	530	290	10	69	162	154	190	215	169~200	10.2
SP - I380	1 (0.75)	620	380	10	69	162	154	190	215	169~200	10.2
SP - Y180	1.5 (1.12)	450	180	10	98	162	154	190	215	169~200	10.2
SP - Y240	1.5 (1.12)	510	240	10	98	162	154	190	215	169~200	10.2
SP - Y290	1.5 (1.12)	560	290	10	98	162	154	190	215	169~200	10.2
SP - Y380	1.5 (1.12)	650	380	10	98	162	154	190	215	169~200	10.2