


Bit Socket



- Socket made by chrome vanadium alloy steel 
- Bit made by silicon alloy steel (S2)
- Polished, chrome plated

3021



- Phillips head
- DIN ISO 8764-1





KT NO.	⊕ No.	Overall length mm		
302102	PH2	50	35	20 / 400
302103	PH3	50	36	20 / 400
302104	PH4	50	37	20 / 400

3022



- Slotted head
- DIN ISO 8764-1





KT NO.	Tip width mm	Tip thickness mm	Overall length mm		
302205	5	1.0	50	36	20 / 400
302208	8	1.2	50	37	20 / 400
302210	10	1.6	50	38	20 / 400

3025



- Hexagon head
- DIN 7422 / 3120





KT NO.	mm	Overall length mm		
302503	H3	50	28	20 / 400
302504	H4	50	30	20 / 400
302505	H5	50	34	20 / 400
302506	H6	50	38	20 / 400
302507	H7	50	38	20 / 400
302508	H8	50	40	20 / 400
302509	H9	50	40	20 / 400
302510	H10	50	40	20 / 400
302512	H12	50	42	20 / 400

3023



- For torx internal screw
- DIN 3120



KT NO.	mm	Overall length mm		
302308	T8	50	28	20 / 400
302309	T9	50	28	20 / 400
302310	T10	50	28	20 / 400
302315	T15	50	28	20 / 400
302320	T20	50	30	20 / 400
302325	T25	50	34	20 / 400
302327	T27	50	38	20 / 400
302330	T30	50	38	20 / 400
302340	T40	50	40	20 / 400
302345	T45	50	40	20 / 400
302350	T50	50	42	20 / 400



In order to get normal life of bit socket, Always use within limited torque to bit.

3027



- For tamper resistant torx screw
- DIN 3120





KT NO.	mm	Overall length mm		
302708	T8H	50	28	20 / 400
302709	T9H	50	28	20 / 400
302710	T10H	50	28	20 / 400
302715	T15H	50	28	20 / 400
302720	T20H	50	30	20 / 400
302725	T25H	50	34	20 / 400
302727	T27H	50	38	20 / 400
302730	T30H	50	38	20 / 400
302740	T40H	50	40	20 / 400
302745	T45H	50	40	20 / 400
302750	T50H	50	42	20 / 400

3039



- Ribe bit socket
- Use for VW, Audi, Fiat cylinder head bolt
- DIN 3120





KT NO.	size	Overall length mm		
303904	M4	90	68	8 / 160
303905	M5	90	69	8 / 160
303906	M6	90	71	8 / 160
303907	M7	90	72	8 / 160
303908	M8	90	88	8 / 160
303909	M9	90	89	8 / 160
303910	M10	90	90	8 / 160

302D



- For torx plus tamper screw
- IPR20 for the operation of the screwed connection of the plug-in pump on MERCEDES-BENZ Atego and Actros MAZDA 3 1.4 and 1.6
- IPR25 for the screwed connections at the control unit and the air flow sensor on VW
- DIN 3120



KT NO.	mm	Overall length mm		
302D08	IPR8	50	33	20 / 400
302D09	IPR9	50	33	20 / 400
302D10	IPR10	50	34	20 / 400
302D15	IPR15	50	34	20 / 400
302D20	IPR20	50	34	20 / 400
302D25	IPR25	50	34	20 / 400
302D27	IPR27	50	34	20 / 400
302D30	IPR30	50	34	20 / 400
302D40	IPR40	50	38	20 / 400
302D45	IPR45	50	38	20 / 400
302D50	IPR50	50	40	20 / 400
302D55	IPR55	50	47	20 / 400
302D60	IPR60	50	51	15 / 300