

## SERVICE JACK(Manual type)

Used at automotive workshops and gas stations the world over.  
All models are equipped with safety valve.

SJ-20S-3  
2ton



SJ-20LL-2  
2ton  
Service Jack(manual type)  
Easier operation by  
installing foot-pedal



SJ-30H  
3ton



## SERVICE JACK(Air type)

Equipped with an air pump that increases working efficiency.  
Easy operation by push-button, especially for use in narrow place.

ASJ-20ML  
2ton

Service Jack,low profile  
(available for air  
and manual type)  
Possible for lift 2 ton load  
from min height.



ASJ-30ML  
3ton

Service Jack,low profile  
(available for air and manual type)  
Possible for lift 3 ton load from  
min height.



ASJ-18M-2S  
1.8ton

Service Jack,low profile  
(available for air and manual type)  
Height can be adjusted by installing  
adjustable screw which is the best to  
avoid damage of lower part of a car.



■ Option (1.5ton~2ton)  
With Nylon wheels.(Low-Noise)



■ Option (3ton,2ton)  
Urethane wheels.(Low-Noise)



## SERVICE JACK SPECIFICATIONS

Spec.	Capacity	Min. Height	Lift.	Max. Height	Height of Frame	Weight	Remarks
Model	(ton)	(mm)	(mm)	(mm)	(mm)	(kg)	
SJ-15H-3	1.5	113	360	473	150	33	
SJ-20S-3	2	113	360	473	150	33	
SJ-20L-2	2	116	360	476	160	45	
SJ-20LL-2 with a pedal	2	98	410	508	120	57	Low profile
SJ-30H with a pedal	3	126	480	606	190	65	
SJ-30LL with a pedal	3	98	515	613	135	80	Low profile
SJ-50H with a pedal	5	150	410	560	200	85	
SJ-100H with a pedal	10	160	400	560	250	135	

## AIR SERVICE JACK SPECIFICATIONS

Spec.	Capacity	Min. Height	Lift.	Max. Height	Height of Frame	Weight	Remarks
Model	(ton)	(mm)	(mm)	(mm)	(mm)	(kg)	
ASJ-18M-2S	1.8	104	505	609	120	61	Low profile
ASJ-20ML	2	98	410	508	120	59	Low profile
ASJ-30M with a pedal	3	126	480	606	190	75	
ASJ-30ML with a pedal	3	98	515	613	135	90	Low profile
ASJ-50M with a pedal	5	150	410	560	200	93	
ASJ-50ML with a pedal	5	115	410	525	150	102	Low profile
ASJ-80ML with a pedal	8	115	445	560	180	140	Low profile
ASJ-100M with a pedal	10	160	400	560	250	140	
※ASJ-150-2	15	175	475	650	230	235	

※Only for air operation

## HYDRAULIC PANTAGRAPH JACK

●For tires replacement · for putting on and taking off a chain.



MSJ-850  
850kg

## HYDRAULIC PANTAGRAPH JACK SPECIFICATIONS

Spec.	Capacity	Min. Height	Lift.	Max. Height	Weight
Model	(kg)	(mm)	(mm)	(mm)	(kg)
MSJ-850	850	121	260	381	5.9

## AIR HYDRAULIC TRUCK JACK

Compact but Powerful · Ideal for heavy duty truck and bus. Rubber wheels for easy maneuverability.

ZATJ-22S-4  
20ton



APJ-250  
25ton



AIR HYDRAULIC PORTABLE JACK  
Light weight and compact  
design for easy portability.

ATJ-350  
35ton



ATJ-200DL-2  
20ton



## AIR HYDRAULIC TRUCK JACK SPECIFICATIONS

Spec.	Capacity	Min. Height	Lift.	Extension Screw Height	Max. Height	Weight	Remarks
Model	(ton)	(mm)	(mm)	(mm)	(mm)	(kg)	
ZATJ-22S-4※	20	198	105	95	398	33	
ATJ-200DL-2	20	143	100	-	243	44	Low profile
ATJ-200	20	210	105	90	405	40	
ATJ-250	25	210	105	90	405	43	
ATJ-350	35	210	100	70	380	45	
ATJ-350L	35	170	80	50	300	43	Low profile
APJ-200-2※	20	210	120	105	435	14	
APJ-250※	25	230	120	105	455	18.5	

※The adapter of ZATJ-22S-4 and APJ-200,250 are option.  
The small and big adapter are standard equipment for other ※mark.