

SPRING BALANCER

TIGON Spring Balancer Improves Work Safety & Efficiency.
Capacities ranging from 0.5~70kg.

TIGON



MODEL	Capacity (kg)	Stroke (m)	Weight (kg)
TW-00	0.5~1.5	0.5	0.2
TW-0	0.5~1.5	1.0	0.5
TW-3	1.0~3.0	1.3	1.4
TW-5	2.5~5.0	1.3	1.5
TW-9	4.5~9.0	1.3	3.4
TW-15	9.0~15.0	1.3	3.8
TW-22	15.0~22.0	1.5	7.2
TW-30	22.0~30.0	1.5	7.6
TW-40	30.0~40.0	1.5	9.8
TW-50	40.0~50.0	1.5	10.4
TW-60	50.0~60.0	1.5	11.6
TW-70	60.0~70.0	1.5	11.8

HOSE REEL BALANCER SERIES



MODEL	Capacity (kg)	Stroke (m)	Weight (kg)	Hose DIA (Ø mm)
HW-0	0.5~1.5	1.3	1.6	Ø6.5 / Ø10
HW-3	1.5~3.0	1.3	1.7	Ø6.5 / Ø10
HW-5	3.0~5.0	1.3	1.8	Ø6.5 / Ø10

-Functions both as balancer and hose reel

RETRACTOR SERIES



MODEL	Capacity (kg)	Stroke (m)	Weight (kg)
RW-0	0.5~1.5	2.0	0.5
RW-3	1.0~3.0	2.0	0.7
RW-5	2.5~5.0	2.0	0.9

-Tension easily adjustable using knob

MODEL	Capacity (kg)	Stroke (m)	Weight (kg)
TW-1R	0.5~1.5	1.5	0.3

-Tension easily adjustable using knob

★ Specifications and designs are subject to change at any time without notice.



F.N.

บริษัท เอฟ เอ็น เอ็นจิเนียริง จำกัด
F.N.ENGINEERING CO.,LTD.

176 Soi Kheharonkiao 64, Klongsongtonnon Ladkrabang,Bangkok.10520

Tel: 0-2918-4441-2,0-2918-3378 [Auto] Hotline 08-1174-3345

Fax: 0-2918-3070,0-2918-2722

Email : sale@fnengineering.com , fnengineer@gmail.com



● For environmental conservation, this print is made of the pulp blended with waste paper and printed with soy-based inks.

Printed in Japan 07EV05-①